

89FEP

Single Display Freestanding Digital Tyre Inflator (with bicycle inflation)

Introducing the new 89FEP inflator model that comes with the choice of dual inflation mode - vehicle and bicycle tyres.

The inflator is very simple to operate. Users can select the switch on the user-friendly control panel, to start the desired inflation for a safe, quick and accurate inflation.

The bicycle inflation hose is equipped with a twin head chuck dedicated for bicycle tyres with Presta/Dunlop or Schrader valves.

Finally an inflator that cyclist can safely use to inflate their tyres.

Please contact Airtec Corporation for further technical information.



NEW
vehicle and bicycle inflator



89FEP

Product Features

- Fast and accurate digital inflation up to 145 psi / 10 bar
- Sleek design with small footprint
- Piezo control switches as standard
- Supplied with 10m hose kit
- Corporate and customised designs available

Technical Specifications

Construction	: Diecast aluminium enclosure (IP46)
Dimension	: 320 W x 1400 H x 320 D mm
Power requirements	: 220V-240VAC (optional 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm ²
Operating range	: 5-145 psi / 35-1000 kPa / 0.3-10.0 bar / 0.4-10.2 kg/cm ²
Reading precision	: 1 psi / 5 kPa / 0.10 bar / 0.1 kg/cm ²
Accuracy	: +/- 0.5% FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)

Optional Accessories



47.0020
Cabinet
Heater (kit)



94.0100
Standard
Tap (kit)



94.0101
Push Button
Tap (kit)



94.0612
Filter
Regulator



91.0202
Twin Head
Chuck